

## CLAIMS

What is claimed is:

1. A method for providing advanced signal processing in a wireless local area network that requires an interframe period between data and an acknowledgement for compatibility, wherein a duration of said interframe period is shorter than a duration that is required to perform said advanced signal processing, comprising:

transmitting a header using a first transceiver;

specifying a first data field in said header that enables said advanced signal processing; and

specifying a second data field that defines a data time period and an extension time period.

2. The method of claim 1 wherein said first data field is a signal portion of said header.

3. The method of claim 1 wherein said second data field is a length portion of said header.

4. The method of claim 1 further comprising transmitting data after said header during said data time period.

5. The method of claim 4 further comprising transmitting dummy data during said extension time period.

6. The method of claim 5 further comprising receiving said header portion at a second transceiver that is located remotely from said first transceiver.

7. The method of claim 6 further comprising initiating receiver processing including said advanced signal processing during said extension time period.

8. The method of claim 1 wherein said advanced signal processing includes advanced error coding.

9. The method of claim 1 wherein said advanced signal processing includes at least one of Turbo coding, Reed-Solomon coding, and convolution coding.

10. The method of claim 1 wherein said interframe period includes time allocated for receiver delay, receiver processing delay, media access control delay, and receiver/transmitter transition delay.

11. The method of claim 10 wherein a time period for said receiver delay and said receiver processing delay are increased by said extension time period.

12. The method of claim 1 wherein said interframe period is specified by at least one of IEEE section 802.11, 802.11(a) and 802.11(b).

U:\Legal\ejanofsky\patapp\MP0133\MP0133 Final Application.doc  
Customer No 23624

13. A method for operating a wireless local area network (WLAN), comprising:

providing a first WLAN transceiver with advanced signal processing capabilities;

providing a second WLAN transceiver with advanced signal processing capabilities, wherein a maximum interframe period between data and an acknowledgement is required for compatibility, and wherein a duration of said interframe period is shorter than a duration that is required to perform said advanced signal processing;

transmitting a header and data using a first transceiver;

specifying a first data field in said header that enables said advanced signal processing; and

specifying a second data field that defines a data time period and an extension time period.

14. The method of claim 13 wherein said first data field is a signal portion of said header.

15. The method of claim 13 wherein said second data field is a length portion of said header.

16. The method of claim 13 further comprising transmitting data after said header during said data time period.

17. The method of claim 16 further comprising transmitting dummy data after said data during said extension time period.

18. The method of claim 17 further comprising receiving said header portion at said second WLAN transceiver that is located remotely from said first WLAN transceiver.

19. The method of claim 18 further comprising initiating receiver processing including said advanced signal processing during said extension time period.

20. The method of claim 13 wherein said advanced signal processing includes advanced error coding.

21. The method of claim 13 wherein said advanced signal processing includes at least one of Turbo coding, Reed-Solomon coding, and convolution coding.

22. The method of claim 13 wherein said interframe period includes time allocated for receiver delay, receiver processing delay, media access control delay, and receiver/transmitter transition delay.

23. The method of claim 22 wherein a time period for said receiver delay and said receiver processing delay are increased by said extension time period.

24. The method of claim 13 wherein said interframe period is specified by at least one of IEEE sections 802.11, 802.11(a) and 802.11(b).

U:\Legal\hejanofsky\patapp\MP0133\MP0133 Final Application.doc  
Customer No. 23624